



Vendor: Cisco

Exam Code: 200-125

Exam Name: CCNA Routing and Switching v3.0

Version: Demo

QUESTION 1

If a host experiences intermittent issues that relate to congestion within a network while remaining connected, which option could cause congestion on this LAN?

- A. multicasting
- B. network segmentation
- C. broadcast storms
- D. half-duplex operation

Correct Answer: C

QUESTION 2

At which layer of the OSI model does the protocol that provides the information that is displayed by the show cdp neighbors command operate?

- A. data link
- B. application
- C. network
- D. transport
- E. physical

Correct Answer: A

QUESTION 3

From which PPPoE server configuration does a PPPoE client get an IP address?

- A. AAA authentication
- B. DHCP
- C. dialer interface
- D. virtual-template interface

Correct Answer: D

QUESTION 4

Which Ethernet interface command is present when you boot a new Cisco router for the first time?

- A. speed 100
- B. shutdown

- C. ip address 192.168.1.1 255.255.255.0
- D. duplex half

Correct Answer: B

QUESTION 5

Which configuration command can you apply to a HSRP router so that its local interface becomes active if all other routers in the group fail?

- A. no additional config is required
- B. standby 1 track ethernet
- C. standby 1 preempt
- D. standby 1 priority 250

Correct Answer: A

QUESTION 6

Which statement about NTP is true?

- A. The default authentication key number is 1.
- B. The default source address of an NTP message is the interface connected to the next- hop for the server peer address.
- C. The default stratum number is 5.
- D. Each device is enabled as a server by default and propagates NTP messages to all peers on its default LAN.

Correct Answer: B

QUESTION 7

Which Cisco SDN controller supports existing enterprise network devices?

- A. APIC-EM
- B. OpenFlow
- C. Open SDN
- D. ACI

Correct Answer: A

QUESTION 8

Which statement about DHCP address pools is true?

- A. A network must be defined before you can configure a manual binding.
- B. Only one DNSserver can be identified for an individual DHCP group.
- C. You can use a subnet mask of prefix length to define a network.
- D. The domain name of the DHCP pool is specified in the global configuration of the router.

Correct Answer: C

QUESTION 9

Which protocol verifies connectivity between two switches that are configured with IP addresses in the same network?

- A. ICMP
- B. STP
- C. VTP
- D. HSRP

Correct Answer: A

QUESTION 10

Which sequence begins a unique local IPv6 address in binary notation?

- A. 11111110
- B. 11111111
- C. 00000000
- D. 11111100

Correct Answer: A

QUESTION 11


Which statement about unique local IPv6 addresses is true?

- A. Summarization is not supported.
- B. They require all prefixes to be unique.
- C. Their global IDs are assigned sequentially.
- D. They are routable to the public Internet.

Correct Answer: B

QUESTION 12

Refer to the exhibit. The enterprise has decided to use the network address 172.16.0.0. The network administrator needs to design a classful addressing scheme to accommodate the three subnets, with 30, 40, and 50 hosts, as shown. Which subnet mask would accommodate this network?




- A. 255.255.255.224
- B. 255.255.255.240
- C. 255.255.255.252
- D. 255.255.255.248
- E. 255.255.255.192

Correct Answer: E

QUESTION 13

Refer to the exhibit. Which switch in this configuration becomes the root bridge?



- A. SW1
- B. SW2
- C. SW3
- D. SW4

Correct Answer: C

QUESTION 14


Which subnet address is for the IP address 172.19.20.23/28?

- A. 172.19.20.20
- B. 172.19.20.0
- C. 172.19.20.32
- D. 172.19.20.15
- E. 172.19.20.16

Correct Answer: E

QUESTION 15

Refer to the exhibit. The exhibit is showing the topology and the MAC address table. Host A sends a data frame to host D. Which option describes what the switch will do when it receives the frame from host A?



- A. The switch will flood the frame out of all ports except for port Fa0/3.
- B. The switch will add the destination address of the frame to the MAC address table and forward the frame to host D.
- C. The switch will add the source address and port to the MAC address table and forward the frame to host D.
- D. The switch will discard the frame and send an error message back to host A.

Correct Answer: C

QUESTION 16

Which statement about 6to4 tunneling is true?

- A. One tunnel endpoint must be configured with IPv4 only.
- B. Both tunnel endpoint must be configured with IPv4 only.
- C. It establishes a point-to-point tunnel.
- D. Both tunnel endpoints must support IPv4 and IPv6.

Correct Answer: D

QUESTION 17

Which two actions must you take to configure a PAgP EthernetChannel between two switches, S1 and S2? (Choose two.)

- A. Configure the channel-group 1 mode auto command on S1.
- B. Configure the channel-group1 mode desirable command on S2.
- C. Configure the channel-group 1 mode active command on S2.
- D. Configure the channel-group 1 mode on command on S2.
- E. Configure the channel-group 1 mode active command on S1.

Correct Answer: AB

QUESTION 18

After you configure a new router to connect to a host through the GigabitEthernet0/0 port of the router, you log in to the router and observe that the new link is down. Which action corrects the problem?

- A. Use a crossover cable between the host and R1.
- B. Use a straight through cable between the host and R1.
- C. Configure the host to use R1 as the default gateway.
- D. Use a rollover cable between the host and R1.

Correct Answer: A

QUESTION 19

Under which two circumstances is network traffic most likely to use an Exterior Gateway Routing Protocol? (Choose two)

- A. When an employee connects to an employer branch office in a different city.

- B. When network traffic is routing to a different building on a corporate campus.
- C. When an employee is browsing the public internet.
- D. When an employee checks email while working onsite at the data center.
- E. When a user browsing the web site of a business partner.

Correct Answer: AD

QUESTION 20

How does a Cisco switch respond if you boot it without a valid configuration in the NVRAM?

- A. it enters setup mode.
- B. it uses the running-configuration
- C. It prompts you to restore the startup configuration
- D. it enters user EXEC mode.

Correct Answer: B

QUESTION 21

Which three statements accurately describe CDP? (Choose three.)

- A. CDP can discover Cisco devices that are not directly connected.
- B. CDP is a network layer protocol.
- C. CDP can discover directly connected neighboring Cisco devices.
- D. CDP is a datalink layer protocol.
- E. CDP is a Cisco proprietary protocol.
- F. CDP is an IEEE standard protocol.

Correct Answer: CDE

QUESTION 22

What is the default encapsulation type for Cisco WAN serial interfaces?

- A. Frame Relay
- B. HDLC
- C. PPP
- D. SDLC

Correct Answer: B