

Ensurepass.com Easy Test! Easy Pass!



Vendor: Cisco

Exam Code: 642-885

Exam Name: Building Cisco Service Provider Next-
Generation Networks, Part 1 (SPNGN1)

Version: DEMO

QUESTION 1

When a BGP route reflector receives an IBGP update from a non-client IBGP peer, the route reflector will then forward the IBGP updates to which other router(s)?

- A. To the other clients only
- B. To the EBGP peers only
- C. To the EBGP peers and other clients only
- D. To the EBGP peers and other clients and non-clients

Answer: C

QUESTION 2

Which two BGP mechanisms are used to prevent routing loops when using a design with redundant route reflectors? (Choose two.)

- A. Cluster-list
- B. AS-Path
- C. Originator ID
- D. Community
- E. Origin

Answer: AC

QUESTION 3

Which two statements correctly describe the BGP ttl-security feature? (Choose two.)

- A. This feature protects the BGP processes from CPU utilization-based attacks from EBGP neighbors which can be multiple hops away
- B. This feature prevents IBGP sessions with non-directly connected IBGP neighbors
- C. This feature will cause the EBGP updates from the router to be sent using a TTL of 1
- D. This feature needs to be configured on each participating BGP router
- E. This feature is used together with the ebgp-multihop command

Answer: AD

QUESTION 4

When implementing source-based remote-triggered black hole filtering, which two configurations are required on the edge routers that are not the signaling router? (Choose two.)

- A. A static route to a prefix that is not used in the network with a next hop set to the Null0 interface
- B. A static route pointing to the IP address of the attacker
- C. uRPF on all external facing interfaces at the edge routers
- D. Redistribution into BGP of the static route that points to the IP address of the attacker
- E. A route policy to set the redistributed static routes with the no-export BGP community

Answer: AC

QUESTION 5

In Cisco IOS-XR, the maximum-prefix command, to control the number of prefixes that can be

installed from a BGP neighbor, is configured under which configuration mode?

- A. RP/0/RSP0/CPU0:P2(config-bgp)#
- B. RP/0/RSP0/CPU0:P2(config-bgp-af)#
- C. RP/0/RSP0/CPU0:P2(config-bgp-nbr)#
- D. RP/0/RSP0/CPU0:P2(config-bgp-nbr-af)#

Answer: D

Ensurepass.com Members Features:

1. Verified Answers researched by industry experts.
2. Q&As are downloadable in PDF and VCE format.
3. 98% success Guarantee and **Money Back** Guarantee.
4. Free updates for **180** Days.

View list of All Exam provided:

<http://www.ensurepass.com/certifications?index=A>

To purchase Lifetime Full Access Membership click here:

<http://www.ensurepass.com/user/register>

Valid Discount Code for 2014: SFOH-FZA0-7Q2S

To purchase the HOT Exams:

| <u>Cisco</u> | | <u>CompTIA</u> | | <u>Oracle</u> | <u>VMWare</u> | <u>IBM</u> |
|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|----------------------------------|----------------------------------|
| <u>100-101</u> | <u>640-554</u> | <u>220-801</u> | <u>LX0-101</u> | <u>1Z0-051</u> | <u>VCAD510</u> | <u>C2170-011</u> |
| <u>200-120</u> | <u>640-802</u> | <u>220-802</u> | <u>N10-005</u> | <u>1Z0-052</u> | <u>VCP510</u> | <u>C2180-319</u> |
| <u>300-206</u> | <u>640-816</u> | <u>BR0-002</u> | <u>SG0-001</u> | <u>1Z0-053</u> | <u>VCP550</u> | <u>C4030-670</u> |
| <u>300-207</u> | <u>640-822</u> | <u>CAS-001</u> | <u>SG1-001</u> | <u>1Z0-060</u> | <u>VCAC510</u> | <u>C4040-221</u> |
| <u>300-208</u> | <u>640-864</u> | <u>CLO-001</u> | <u>SK0-002</u> | <u>1Z0-474</u> | <u>VCP5-DCV</u> | <u>RedHat</u> |
| <u>350-018</u> | <u>642-467</u> | <u>ISS-001</u> | <u>SK0-003</u> | <u>1Z0-482</u> | <u>VCP510PSE</u> | <u>EX200</u> |
| <u>352-001</u> | <u>642-813</u> | <u>JK0-010</u> | <u>SY0-101</u> | <u>1Z0-485</u> | | <u>EX300</u> |
| <u>400-101</u> | <u>642-902</u> | <u>JK0-801</u> | <u>SY0-301</u> | <u>1Z0-580</u> | | |
| <u>640-461</u> | <u>700-302</u> | | | <u>1Z0-820</u> | | |

