



Exam Code: 050-850

Exam Name: Cni-internet security mgmt
w/bordermanager:enterpr

Vendor: NOVELL

Version: DEMO

Part: A

1: What is a benefit of using a VPN to connect 2 sites over the internet?

- A.Costs are significantly less than using dedicated private lines.
- B.Access speed is significantly increased for site to site communications.
- C.Worldwide 128-bit data encryption is automatically used between VPN sites.
- D.Packets are fragmented and sent along different data paths so even if some packets are intercepted security is not compromised.

Correct Answers: A

2: Application proxy services in BorderManager offer what main features? (Choose 2.)

- A.Proxy caching
- B.User licensing
- C.Access control
- D.Virtual Proxy Networking (VPN)
- E.Proxy Address Translation (PAT)

Correct Answers: A C

3: Which packet types do IP packet forwarding filters recognize? (Choose 3.)

- A.TCP
- B.UDP
- C.NCP
- D.RIP
- E.SAP
- F.ICMP

Correct Answers: A B F

4: Which tasks are involved in defining a security policy? (Choose 3.)

- A.Implement a VPN
- B.Identify the threats
- C.Compare software solutions
- D.Identify network resources
- E.Identify unauthorized access

Correct Answers: B D E

5: Which application proxy types transfer data without caching it? (Choose 2.)

- A.FTP
- B.DNS
- C.Mail
- D.News
- E.HTTP

Correct Answers: C D

6: Transparent proxy can be implemented for which application proxy services? (Choose 2.)

- A.FTP
- B.Mail
- C.News
- D.HTTP
- E.Telnet

Correct Answers: D E

7: Which server console command would you use to test routes to specific IP destinations?

Correct Answers: IPTRACE.NLM

8: Which firewall component implements access control at the session layer of the OSI model?

- A.Domain routers
- B.Application proxies
- C.IP filtering routers
- D.Circuit-level gateways
- E.Packet filtering routers

Correct Answers: D

9: Which firewall component is referred to as a screening router?

- A.Domain router
- B.Circuit gateway
- C.IP gateway router
- D.Application proxy
- E.Packet filtering router

Correct Answers: E

10: With BorderManager on your token ring network, the maximum physical receive packet size is set to 4202. You need to change this setting to allow for a PPP header. What will the new maximum physical receive packet size be after you make this change?

- A.4207
- B.4210
- C.4212
- D.4302
- E.5202

Correct Answers: C