



Exam Code: 090-600

Exam Name: SCO OpenServer Release 6 System

Administration

Vendor: SCO

Version: DEMO

Part: A

1: In SCO OpenServer Release 6, which file specifies the system default login shell for new user accounts created with scoadmin(ADM)?

- A./etc/default/accounts
- B./etc/default/authsh
- C./usr/lib/mkuser/accounts
- D./usr/lib/mkuser/authsh

Correct Answers: A

2: In SCO OpenServer Release 6, which files are used to create the user-specific environment files for the Korn shell?

- A./etc/profile and /etc/kshrc
- B./etc/default/profile and /etc/default/kshrc
- C./usr/lib/ksh/profile and /usr/lib/ksh/kshrc
- D./usr/lib/mkuser/ksh/profile and /usr/lib/mkuser/ksh/kshrc

Correct Answers: D

3: If a user has a umask value of 027, what will be the permissions of any new regular file created by that user?

- A.-rw-r----
- B.-rwxr-x---
- C.----w-rw-
- D.----w-rwx

Correct Answers: A

4: To provide compatibility with other UNIX systems, what is the suggested maximum length of a user login name?

- A.8
- B.3
- C.5
- D.12

Correct Answers: A

5: In SCO OpenServer Release 6, which utility is used to create a user?

- A.scosh(C)
- B.rusers(ADM)
- C.passwd(C)
- D.scoadmin(ADM)

Correct Answers: D

6: Which command can be used to reactivate a retired user account on a system with a security profile set to traditional?

- A.activate(ADM)

- B.restore(ADM)
- C.unretire(ADM)
- D.A retired account cannot be reactivated.

Correct Answers: C

7: What does the system do with the users home directory and its contents when a user account is deleted using the scoadmin(1M) Account Manager?

- A.The home directory and its contents are moved to the /etc/security/ia directory.
- B.The home directory and its contents are automatically stored on an archive medium of your choice.
- C.The home directory and its contents are left in their original location.
- D.The home directory and its contents are automatically deleted.

Correct Answers: C

8: For Bourne and Korn shell users, one of the PERSONAL startup files is:

- A.\$HOME/.login
- B.\$HOME/.profile
- C./etc/login
- D./etc/profile

Correct Answers: B

9: In SCO OpenServer Release 6, which command locks a user account?

- A.accton(ADM)
- B.lock(C)
- C.passwd(C)
- D.scolock(X)

Correct Answers: C

10: Peter has a login name peter and is a member of the group admin. Given the following output from ls(1), what does he currently have permission to do with the file named datafile? -r--rw---x 1 peter admin 7042 Aug 3 13:23 datafile

- A.He can only read from the file.
- B.He can only write to the file.
- C.He can only execute the file.
- D.He can both read from and write to the file.

Correct Answers: D

11: Which term best describes a system process that runs in the background?

- A.daemon
- B.defunct
- C.parent
- D.zombie

Correct Answers: A

12: How can you identify most daemon processes from the output of the following command: ps -ef

- A. There is a UID of system.
- B. There is a ? in the tty column.
- C. There is a d in the status column.
- D. There is a PID greater than 500.

Correct Answers: B

13: Which signal is sent to process 532 when root issues the command: kill 532

- A. 1
- B. 3
- C. 9
- D. 15

Correct Answers: D

14: By convention, which signal is sent when you press the key?

- A. 2
- B. 3
- C. 9
- D. 15

Correct Answers: A

15: In SCO OpenServer Release 6, which option to crontab(C) allows you to edit a crontab entry directly?

- A. -e
- B. -l
- C. -r
- D. -u

Correct Answers: A

16: Which directory contains the system default crontab files?

- A. /etc/default
- B. /usr/spool/cron/crontabs
- C. /usr/lib/scoadmin/tasksched
- D. /usr/lib/scoadmin/defaults

Correct Answers: B

17: Which task can NOT be completed using the scoadmin(1M) Process Manager?

- A. Kill a selected process
- B. View all processes sorted by user
- C. Change the nice(1) value of an executing process
- D. Schedule a process for unattended execution

Correct Answers: D

18: In SCO OpenServer Release 6, what is the default filesystem type for the root filesystem?

- A.AFS (Acer Fast Filesystem)
- B.vxfs (Veritas Filesystem)
- C.EAFS (Extended Acer Fast Filesystem)
- D.HTFS (High Throughput Filesystem)

Correct Answers: B

19: What does the following mount(ADM) command do: mount -r /dev/fd0 /mnt

- A.It mounts /dev/fd0 as a read-only filesystem at mount point /mnt.
- B.It recursively mounts the directories on /dev/fd0.
- C.It removes /dev/fd0 from the mount point /mnt.
- D.It gives the status of /dev/fd0.

Correct Answers: A

20: When should the fsck(ADM) utility be run on the /dev/u filesystem?

- A.At least once each hour on a heavily used machine
- B.Only when it is unmounted
- C.Only when it is mounted
- D.Before it is unmounted

Correct Answers: B