

Exam Code: 1T6-222 Exam Name: Wireless LAN Analysis and Troubleshooting Vendor: Network General Corp Version: DEMO

Part: A

1: ETSI BRAN is directly responsible for which wireless technology? A.Bluetooth B.HiperLAN2 C.HomeRF SWAP D.WECA **Correct Answers: B**

2: IEEE 802.11b supports the following data packet rates:
A.1, 2, 5.5, and 11 Mbps
B.1, 2, 5, and 11 Mbps
C.1, 2.5, 5 and 11 Mbps
D.1, 2, 5 and 11.5 Mbps
Correct Answers: A

3: Access Points do NOT do the following:
A.Forward frames between wireless and/or wire-attached stations
B.Buffer frames for stations out of range or in power save mode
C.Route frames between different subnets
D.Forward frames between wireless devices on the same subnet
Correct Answers: C

4: An Extended Service Set configuration includes which of the following devices?
A.Mobile units and multiple Access Points connected to wired LANs
B.Mobile units with no Access Points
C.Mobile devices and a single Access Point connected to a wired LAN
D.Multi-homed mobile devices
Correct Answers: A

5: Which three of the following devices support 802.11b WLAN software and hardware? (Select three that apply)
A.Desktop PC
B.Laptop PC
C.Analog cellular telephone
D.Personal Digital Assistant
Correct Answers: A B D

6: What data transfer rates does IEEE 802.11a support?
A.1 and 2 Mbps
B.1, 2.5, 5 and 11 Mbps
C.6 to 54 Mbps
D.1, 2, 5 and 11.5 Mbps
Correct Answers: C

7: Which Expert layer does NOT show wireless objects ?
A.Application
B.Session
C.Connection
D.Global
Correct Answers: D

8: Which Monitor display shows the channel each device is using? A.Host Table > MAC tab B.Global Statistics > Channel Surfing tab C.Host Table > 802.11 tab D.Global Statistics > Utilization Dist. tab **Correct Answers: C**

9: Which Monitor display shows various counts and the BSSID on each channel?
A.Global Statistics > Channel Surfing tab
B.Matrix > Channel Surfing tab
C.Dashboard > Channel Surfing tab
D.Protocol Distribution > Channel surfing tab
Correct Answers: A

10: Which Monitor application shows the minimum, maximum and current signal strength of each device?

A.Matrix > MAC Detail B.Global Statistics > Channel Surfing tab C.Host Table > 802.11 tab D.Multiple History Samples **Correct Answers: C**

11: True or false? You must use both a wireless and Ethernet card to monitor and sniff a wireless network.

A.True B.False **Correct Answers: B**

12: You can set wireless triggers using which three criteria? (Select three that apply)
A.Enable Alarms, then choose various wireless frame types
B.Choose a previously defined capture filter
C.Enable Alarms, then choose the channel you wish to observe
D.Enable channel surfing, then use a station address filter
Correct Answers: A B D

13: What is the minimum RAM recommended for a Sniffer Portable with a wireless interface?

A.32 MB B.64 MB C.128 MB D.256 MB **Correct Answers: C**

14: Which path is used to enable Sniffer Portable to capture on specific BSSID and ESSIDs?
A.Capture > Options > 802.11 tab
B.Capture > Define filter > 802.11 tab
C.Tools > Options > 802.11 tab
D.Capture > Tools > 802.11 tab
Correct Answers: C

15: Sniffer Wireless shows full seven-layer decodes for all frames if you:
A.Enter the correct WEP key before you open a trace file
B.Entered the correct WEP key before the frames were captured
C.Use Display > Display Setup > Summary Display > Decrypt all frames
D.Use Display > Display Setup > Summary Display and enable 802.11 protocols
Correct Answers: B

16: Which statement is correct about Sniffer Portables ability to work with WEP encrypted frames?

A.Sniffer Portable cannot decode WEP encrypted data frames

B.Sniffer Portable can decode entire encrypted frames if you have entered the correct WEP keys

C.Sniffer Portable can decode only the DLC and network layer of encrypted frames if you have entered the correct WEP keys

D.Sniffer Portable supports only 40-bit WEP encryption

Correct Answers: B

17: Which PHY medium specifies Dwell Time?A.IRSSB.FHSSC.InfraredD.DSSSCorrect Answers: B

18: View the exhibit of a Decode window view of a frame below.

DLC: FRAME ERROR	5 50.9460; frame size is 1540 (0604 hex) bytes = Bad CRC = 99 %
DLC: Channel DLC: Data rate DLC: Short Preamble DLC: Frame Originally Encrypted	= 6 = 22 (11.0 Megabits per second) d

What is the transmitted data rate for this frame?

A.1 Mbps B.2 Mbps C.5.5 Mbps D.11 Mbps **Correct Answers: D**

19: Choose all that apply. Which techniques are used by moving devices to reserve air time?
A.Virtual Carrier Sense
B.Contention-Free
C.Power Save
D.RTS, CTS frames
Correct Answers: A D

20: View the exhibit of a Decode window view of a frame below.

```
DLC: Frame Control Field #1 = 08
                DLC:
                 .... 10.. = 0x2 Data Frame
) DLC :
DLC: 0000 .... = 0x0 Data (Subtype)
DLC: Frame Control Field #2 = 01
                ..... 1 = To Distribution System
) DLC:
                ) DLC:
                DLC :
                .... 0... = Not retry
) DLC :
 DLC
                ...0 .... = Active Mode
                ...0. .... = No more data
 DLC:
                 .0., .... = Wired Equivalent Privacy is off
) DLC :
                0.... = Not ordered
DLC
```

How is this frame being delivered?

A.From the mobile unit to the Access Point

B.From the Access Point to the mobile unit

C.From the mobile unit to another mobile unit in ad hoc mode

D.From a wired station to the Access Point

Correct Answers: A