



Vendor: Cisco

Exam Code: 350-030

Exam Name: Cisco CCIE Voice Written v3.0

Version: Demo

QUESTION 1

What are two advantages of multicast technologies? (Choose two.)

- A. Denial of service attacks in the network are prevented.
- B. They eliminate multipoint applications.
- C. They reduce traffic by delivering a separate stream of information to each corporate recipient or home environment, which reduces bandwidth.
- D. They control network traffic and reduce server and CPU load.
- E. They eliminate traffic redundancy.

Correct Answer: DE

QUESTION 2

Which two descriptions apply to the Calling Search Space function in Cisco Unified Communications Manager? (Choose two.)

- A. It defines which numbers are available for a device to call.
- B. It provides a group of dial patterns to look through when making a call.
- C. Within a partition, each CSS has a directory number.
- D. It defines route patterns and directory numbers from which calls can be received.
- E. It defines the search for directory numbers in assigned partitions according to dial patterns.

Correct Answer: AE

QUESTION 3

Which two statements apply to the partitions function in Cisco Unified Communications Manager? (Choose two.)

- A. When a directory number or route pattern is placed into a certain partition, this creates a rule for who can call that device or route list.
- B. A partition is a logical grouping of directory numbers and route patterns that have similar reachability characteristics.
- C. Calling Search Spaces are assigned to partitions.
- D. A directory number may appear in only one partition.
- E. Within the partition, each CSS has a directory number.

Correct Answer: AB

QUESTION 4

Which three statements are true about multicast IGMP snooping? (Choose three.)

- A. When a host in a multicast group sends an IGMP leave message, only that port is deleted from the multicast group.
- B. An IP multicast stream to the IP host can be stopped only by an IGMP leave message.
- C. IGMP snooping does not examine or snoop Layer 3 information in packets that are sent between the hosts and the router.
- D. When the switch hears the IGMP host report from a host for a particular multicast group, the switch adds the host's port number to the associated multicast table entry.
- E. IGMP control messages are transmitted as IGMP multicast packets so that they can be distinguished from normal multicast data at Layer 2.
- F. A switch that is running IGMP snooping examines every multicast data packet to verify whether it contains any pertinent IGMP "must control" information.

Correct Answer: ADF

QUESTION 5

Which three options are valid SCCP call states sent to an IP phone?

- A. Ring Off
- B. On Hook
- C. Call Transmit
- D. Connected
- E. Disconnected
- F. In Use Remotely

Correct Answer: BDF

QUESTION 6

Which three statements are true about Cisco Discovery Protocol? (Choose three.)

- A. It is an excellent tool for displaying the interface status on switches.
- B. It works on top of the network layer and data link level.
- C. It uses a multicast packet with a destination MAC address of 01-00-CC-CC-CC.
- D. The platform TLV (TLV type 0x0006) contains an ASCII character string that describes the hardware platform of the device.
- E. You can use the CDP timer feature to change update times. The default is 60 seconds.
- F. It uses a broadcast packet with a destination MAC address of 01-00-CC-CC-CC.

Correct Answer: ADE

QUESTION 7


Which two of the following are functions of DHCP snooping? (Choose two.)

- A. relies on already discovered trusted and untrusted ports
- B. dynamic ARP inspection
- C. defines trusted and untrusted ports
- D. uses existing binding tables
- E. builds a binding table
- F. automatically builds ACLs

Correct Answer: CE

QUESTION 8

Refer to the exhibit. Traffic flows from the IP phone that is connected to SW1 to the IP phone on SW2. If the trust boundary has been extended to the IP phone on SW1, in what two places will traffic be marked and classified so that the proper QoS settings may be carried through the network? (Choose two.)




- A. IP phone attached to SW1
- B. SW1 ingress port
- C. R1 ingress port
- D. SW1 egress port
- E. R1 egress port

Correct Answer: BC

QUESTION 9

Refer to the exhibit. Which gatekeeper mechanism prevents the gatekeeper from using all the resources on either gateway 1 or gateway 2 when sending calls to zones SE and NW?



- A. bandwidth remote
- B. resource availability indicator
- C. bandwidth total
- D. bandwidth zone
- E. irq immediate advance
- F. ras timeout brq

Correct Answer: B

QUESTION 10

When implementing a Cisco Unified Communications Manager solution over an MPLS WAN, which two rules must be observed to prevent overrunning the priority queue? (Choose two.)

- A. RSVP will transparently pass application IDs from the customer network across the MPLS WAN.
- B. The media streams must be the same size in both directions.
- C. Only the connection to the MPLS WAN where the Cisco Unified Communications Manager resides must be enabled as a CE device.
- D. The media has to be symmetrically routed.
- E. If the CE is under corporate control, it may support either topology-aware or measurement-based CAC.

Correct Answer: BD

QUESTION 11


How is fax pass-through traffic treated over IP WAN connections that use the G.729 codec?

- A. The fax traffic is demodulated and sent with VAD and echo cancellor disabled.
- B. When the TGW detects the CED tone from the fax machine that has been contacted, the TGW changes to the G.711 codec with echo cancellor and VAD disabled.
- C. When the OGW detects the CED tone from the fax machine that is making the call, the OGW is informed by the contacted device of the Cisco NSF features and switches to the G.711 codec with VAD disabled.
- D. The contacting fax machine sends a TCF message to the contacted fax machine and waits for a CFR message. When the CFR message is received, the fax tones sent by the contacting fax machine cause the OGW to send an NSF message to the TGW, instructing it to switch to the G.711 codec with echo cancellor and VAD disabled.

Correct Answer: B

QUESTION 12

Refer to the exhibit. How many simultaneous G.729 calls can be established between sites SJ and RTP?



- A. 4
- B. 5
- C. 6
- D. 8

E. 12

Correct Answer: C

QUESTION 13

Company Alpha has a central office and a branch office that utilize a central call processing topology. Calls between the two sites are using the G.729 codec; calls within each site are using the G.711 codec. To conference an existing call between two phones at the central site with a phone at the remote office, which two of the following are possible solutions? (Choose two.)

- A. a software conference bridge that is configured in Cisco Unified Communications Manager
- B. a software conference bridge that is configured in Cisco Unified Communications Manager and a HW transcoder
- C. a hardware conference bridge
- D. a hardware transcoder and a hardware conference bridge
- E. No extra configurations required--phones automatically negotiate using the lowest common denominator codec (G.729)

Correct Answer: BC

QUESTION 14


Which two of these are possible reasons why a JTAPI subsystem might have the status PARTIAL_SERVICE? (Choose two.)

- A. Cisco Unified Contact Center is not able to resolve the host name of Cisco Unified Communications Manager.
- B. A referenced CTI Route Point is not associated with the JTAPI user.
- C. The JTAPI user password is not correct.
- D. There is an error in one of the scripts being loaded.
- E. The CTI Manager service is not running on Cisco Unified Communications Manager.

Correct Answer: BD

QUESTION 15

Refer to the exhibit. You have been asked to edit the sample auto attendant script so that callers are prompted to press 1 for sales, 2 for service, or 3 for the directory. If callers select 3, they should hear the existing menu choices to dial by extension, dial by name, or transfer to the operator. What steps can you take to create this nested menu?



- Drag a new Menu step from the palette and drop it on the Start step. Drag the existing Menu step and drop it on Output 3 of the new Menu.
- Drag a new Menu step from the palette and drop it on the existing Menu step. This will make the existing Menu subordinate to the new Menu.
- Drag a new Menu step from the palette and drop it on the existing Menu step. Drag the existing Menu step and drop it on Output 3 of the new Menu.
- Delete the existing Menu. Drag a new Menu step from the palette and drop it on the Set prefixPrompt=P[] step. Recreate the existing directory menu as the third option of the new Menu step.

Correct Answer: C

QUESTION 16

Which three of these are mandatory sub-commands of the call-manager-fallback command and will help an IP phone register to an IOS router in SRST mode? (Choose three.)

- A. access-code
- B. dialplan-pattern
- C. ip source-address
- D. keepalive
- E. max-dn
- F. max-ephones

Correct Answer: CEF

QUESTION 17

Refer to the exhibit. You are debugging a problem on a SIP network and have run the debug ccsip messages command. One of the messages returned is shown in the exhibit. What information will the server return to the caller?

```
May 9 02:13:06.370:
Send:
 SIP/2.0 415 Unsupported media type
Via: SIP/2.0/UDP 10.0.1.3:54475
From: sip:7300001@10.0.1.3
To: <sip:7900001@10.0.2.3;user=phone>;tag=9B9374-18BE
Date: Tue, 09 May 1993 02:13:06 UTC
Call-ID: 7B8D93F2-6EE5001E-0-9BCB54@10.0.1.3
Server: Cisco VoIP Gateway/ IOS 12.x/ SIP enabled
Content-Type: application/sdp
CSeq: 100 INVITE
Content-Length: 442
```

- A. the acceptable media type
- B. a list of acceptable media types
- C. a list of acceptable formats
- D. a correct directory number
- E. an acceptable language code

Correct Answer: C

QUESTION 18

Which type of SIP responses would indicate that a server encountered an error in attempting to complete a SIP request?


- A. 1xx

- B. 3xx
- C. 4xx
- D. 5xx
- E. 6xx

Correct Answer: D

QUESTION 19

To hide its identity when initiating calls, SIP Phone B requests that Server B place its calls for it. What kind of device is Server B?




- A. proxy
- B. redirect
- C. registrar
- D. user agent client
- E. user agent server

Correct Answer: A

QUESTION 20

Which of the following three messages could be sent by the UAC in response to the 180 Ringing? (Choose three.)



- A. PRACK
- B. ACK

- C. BYE
- D. CANCEL
- E. INVITE

Correct Answer: ABD

QUESTION 21

Which three attributes correctly describe aspects of MGCP? (Choose three.)

- A. peer-to-peer
- B. Master/Slave
- C. call preservation on gateway failover from one Cisco Unified Communications Manager server to another
- D. communication with Cisco Unified Communications Manager handled via a proxy server
- E. centralized dial plan management
- F. intelligent endpoints

Correct Answer: BCE

QUESTION 22

In a VoIP deployment, which two protocols satisfy the following three requirements? (Choose two.)

Requirement 1: the protocol has a mechanism for a centralized dial-plan

Requirement 2: the endpoints are considered to be unintelligent

Requirement 3: the protocol is text-based

- A. SIP
- B. H.323
- C. MGCP
- D. SCCP

Correct Answer: CD

QUESTION 23

When implementing PRI backhaul for an MGCP gateway and Cisco Unified Communications Manager, the Q.921 data-link protocol is terminated on which device?

- A. Cisco Unified Communications Manager
- B. MGCP gateway
- C. signaling link terminal
- D. the IP end device, such as an IP phone

Correct Answer: B

QUESTION 24

What occurs if the system clocks are not synchronized between the sender and receiver of an RTP stream?

- A. Packets can be placed in sequence but jitter cannot be compensated for.
- B. Packets cannot be reordered, because sequence and jitter cannot be compensated for.
- C. Jitter can be compensated for, but packets cannot be reordered if they arrive out of sequence.
- D. Packets may be reordered and jitter may be compensated for, because the timestamp is not related to the system time.
- E. When the RTP stream is opened, the sender and receiver synchronize their clocks before the stream commences so that packet sequencing and dejitter will function correctly.

Correct Answer: D

QUESTION 25

On which gateway or gatekeeper is the IOS command `call-rsvp-sync resv-timer 10` used to set the timer?

- A. originating VoIP gateway for completing RSVP reservation setups in 10 seconds
- B. originating and terminating VoIP gateway for completing RSVP reservation setups in 10 seconds
- C. terminating VoIP gateway for completing RSVP reservation setups in 10 seconds
- D. VoIP gatekeeper for completing RSVP reservation setups in 10 seconds

Correct Answer: C

QUESTION 26

If the `bandwidth total default 64` command is configured in a gatekeeper, then what is true of that gatekeeper?

- A. it will admit up to 64 calls, regardless of codec used
- B. it will not admit any calls because all calls initially account of 128 kb/s
- C. it will admit a minimum of four calls using the G.729 codec
- D. it will admit up to four calls using the G.729 codec
- E. it will admit a G.711 call in one direction only, since 64 is half of 128 kb/s

Correct Answer: D

QUESTION 27

If enabled, the RSVP for LLQ feature will assign which two types of flows to the priority queue? (Choose two.)

- A. all RSVP bandwidth requests
- B. voice flows generated from Cisco IOS applications
- C. voice flows generated from third-party applications, such as Microsoft NetMeeting
- D. all traffic marked DSCP EF
- E. all traffic marked CoS 5

Correct Answer: BC

QUESTION 28

Which of these features are supported in RSVP Support for LLQ? (Choose three.)

- A. LLQ Support on Tunnels
- B. Guaranteed Quality of Service
- C. Reserve resources for Low Latency and bandwidth guarantees
- D. LLQ on Frame Relay and ATM PVCs
- E. Controlled-Load Network Element Service

Correct Answer: BCE

QUESTION 29

Users are complaining that the music on hold marketing files for this month are not being played when users are placed on hold. Which three of these do you need to verify? (Choose three.)

- A. the IP voice media streaming application has been stopped and restarted
- B. a new directory has been created for the new media files
- C. users have selected the correct MoH files for customer calls
- D. the new music files are in the correct format to be used with Cisco Unified Communications Manager
- E. the location of the new music files is what the MoH server expects

Correct Answer: ADE

QUESTION 30

Which of these statements correctly describes the logic for selecting MoH servers and MoH audio streams?

- A. The audio stream and audio server used will be selected according to the configuration of

the phone being placed on hold.

- B. The audio stream and audio server used will be selected according to the configuration of the phone which is being used to place a caller on hold.
- C. The audio stream will be selected according to the configuration of the phone which is being used to place a caller on hold, and the audio server used will be selected according to the configuration of the phone being placed on hold.
- D. The audio stream will be selected according to the configuration of the phone being placed on hold and the audio server used will be selected according to the configuration of the phone which is being used to place a caller on hold.

Correct Answer: C

EnsurePass.com Members Features:

1. Verified Answers researched by industry experts.
2. Q&As are downloadable in PDF and VCE format.
3. 98% success Guarantee and **Money Back** Guarantee.
4. Free updates for **180** Days.
5. **Instant Access to download the Items**

View list of All Exam provided:

<http://www.ensurepass.com/certifications?index=A>

To purchase Lifetime Full Access Membership click here:

<http://www.ensurepass.com/user/register>

Valid Discount Code for 2015: JREH-G1A8-XHC6

To purchase the HOT Exams:

<u>Cisco</u>		<u>CompTIA</u>		<u>Oracle</u>	<u>VMWare</u>	<u>IBM</u>
100-101	640-554	220-801	LX0-101	1Z0-051	VCAD510	C2170-011
200-120	200-101	220-802	N10-005	1Z0-052	VCP510	C2180-319
300-206	640-911	BR0-002	SG0-001	1Z0-053	VCP550	C4030-670
300-207	640-916	CAS-001	SG1-001	1Z0-060	VCAC510	C4040-221
300-208	640-864	CLO-001	SK0-003	1Z0-474	VCP5-DCV	RedHat
350-018	642-467	ISS-001	SY0-301	1Z0-482	VCP510PSE	EX200
352-001	642-813	JK0-010	SY0-401	1Z0-485		EX300
400-101	642-832	JK0-801	PK0-003	1Z0-580		
640-461	642-902			1Z0-820		

