



**Exam Code:** 920-502

**Exam Name:** nncss-optera metro 3000

**Vendor:** Nortel

**Version:** DEMO

## **Part: A**

1: Which statement is true about the relationship between facilities and equipment on the OPTera Metro 3000?

- A. Facilities are the individual signal ports located on an equipment circuit pack card.
- B. Facilities are the buildings or locations where the OPTera Metro equipment is installed.
- C. Facilities are the I/O modules associated with the circuit pack located in the corresponding slot on the shelf.
- D. OPTera Metro 3000 recognizes equipment specifications but allows the facilities option to determine maximum capacities.

**Correct Answers: A**

2: You have a three-node USPR network with OC-12 line rate. Which pass through cross-connect is valid?

- A. fromAID = OC12-11-1; toAID = DS3-9; CCT = 2WAY
- B. fromAID = OC12-11-1; toAID = OC12-12-1; CCT = 2WAYPR
- C. fromAID = OC12-11-1-1-1; toAID = OC12-12-1-1-1; CCT = 2WAY
- D. fromAID = OC12-11-1-1-1; toAID = OC12-12-1-1-1; CCT = 2WAYPR

**Correct Answers: C**

3: You want to reprovision a shelf with DS3s instead of DS1s. How do you delete a PSC from an OPTera Metro 3500 shelf?

- A. All DS1 facilities must be put out-of-service before the PSC can be put out-of-service and deleted.
- B. All DS1 and DS3 facilities must be put out-of-service before the PSC can be put out-of-service and deleted.
- C. All DS1 facilities and equipment must be put out-of-service and deleted before the PSC can be put out-of-service and deleted.
- D. All DS1 and DS3 facilities and equipment must be put out-of-service and deleted before the PSC can be put out-of-service and deleted.

**Correct Answers: C**

4: One NE on an OPTera Metro 3500 network is having problems being accessed from a remote NP. What is the problem?

- A. The NE is not on the NP's SOC.
- B. The wrong date and time is set for the afflicted NE.
- C. The afflicted NE has a non-unique system identifier.
- D. The IP address of the afflicted NE is on the wrong subnet.

**Correct Answers: C**

5: You are fibering a Band 1 OMX module. How is the "Channel 1 Add port" utilized in order to allow Band 1 Channel 1 traffic signals to be added and dropped at a site?

- A. This port is connected to the Band 1 OMX module OTS out port.
- B. This port is connected to the Band 1 Channel 1 drop port of the Band 1 OMX module.

- C.This port is connected to the receive port of a Band 1 Channel 1 OC-48 optical circuit pack.
- D.This port is connected to the transmit port of a Band 1 Channel 1 OC-48 optical circuit pack .

**Correct Answers: D**

6: You have a protected four-channel DWDM implementation on the OPTera Metro 3500 platform. What is the minimum number of OMX modules required at the terminal site?

- A.one
- B.two
- C.three
- D.four

**Correct Answers: B**

7: You are dispatched to solve a problem with an OPTera Metro 3000 network. You checked the fiber connections and found that the fiber pair from slot 11 on one shelf is always connected to slot 12 of the next shelf. Which network topology has been configured?

- A.UPSR configuration
- B.Linear ADM configuration
- C.Folded-Ring configuration
- D.Matched-Node configuration

**Correct Answers: A**

8: Which timing source is best quality for use at the head-end in an OPTera Metro 3500 network?

- A.SMC quality line source
- B.ST4 quality BITS source
- C.ST2 quality BITS source
- D.internal timing from VTX-48

**Correct Answers: C**

9: A customer requests eight EIM bridge ports on an OPTera Metro 3300 shelf that has an OC-12 line rate. Which combination of I/O modules and circuit packs is required?

- A.EIM circuit packs in slots 3, 4, 5, and 6 and the RIO with the Ethernet adapter modules P2 and P4
- B.EIM circuit packs in slots 3, 4, 5, and 6 and the LIO with the Ethernet adapter modules P2 and P4
- C.EIM circuit packs in slots 7, 8, 9, and 10 and the RIO with the Ethernet adapter modules P2 and P4
- D.EIM circuit packs in slots 7, 8, 9, and 10 and the LIO with the Ethernet adapter modules P2 and P4

**Correct Answers: C**

10: You have DS3 circuit packs installed in slots 7 and 8 in an OPTera Metro 3300. Which BNC connectors should you use to connect the incoming and outgoing signals?

- A.port 2 on the left I/O
- B.port 2 on the right I/O

- C.port 7 on the top I/O
- D.port 7 on the left I/O

**Correct Answers: A**

11: A new application was introduced to manage the OPTera Metro 3500. What is the application called?

- A.BCC
- B.PCGUI
- C.Preside Site Manager
- D.Preside System Manager

**Correct Answers: C**

12: What are three functions of the MTX circuit pack? (Choose three.)

- A.DS1 mapping
- B.DS3 mapping
- C.shelf communications and alarms
- D.optical connectivity at the OC-3 rate
- E.synchronization and bandwidth management

**Correct Answers: A D E**

13: A Remote Alarm(s) alarm is raised on the SP. Which event has occurred?

- A.The NP has been removed.
- B.The SP is not in the NP's SOC.
- C.An NP facility, such as a COLAN port, has failed.
- D.The SP has detected an unauthorized remote login attempt.

**Correct Answers: C**

14: Which connectors are available on the Top I/O on the OPTera Metro 3400?

- A.DS1 connectors for ports 1 through 28
- B.DS1 connectors for ports 29 through 84
- C.BNC connectors for DS3s in slots 7 through 10
- D.BNC connectors for ports 2 and 3 for DS3x3 circuit packs

**Correct Answers: D**

15: The NOC has lost association to an OPTera Metro 3000 shelf. Which method should you use to access the affected shelf?

- A.select the icon on the user interface and click Connection, Refresh
- B.connect a PC directly to the SP using a modem cable and log in to the shelf
- C.log in to the NP that has this shelf in its span of control and then log in to the shelf
- D.from the user interface, log in to a neighbor node and then log in to the problem shelf

**Correct Answers: B**