



Exam Code: e20-532

Exam Name: networked storage-san specialist exam for
storage admins

Vendor: EMC

Version: DEMO

Part: A

1: Click the Task button.

Match each diagram (A, B, C) to the switch topology.

Match each diagram (A, B, C) to the switch topology.

A **B** **C**

place here place here place here

Topology labels to be moved

Core-Edge Direct Attach Switched Fabric Arbitrated Loop Done

Correct Answers:

Match each diagram (A, B, C) to the switch topology.

A **B** **C**

Direct Attach Arbitrated Loop Switched Fabric

Topology labels to be moved

Core-Edge Direct Attach Switched Fabric Arbitrated Loop Done

2: Which Cisco tool is used to monitor, configure and manage multiple MDS switches?

A.Device Tools

- B.SAN Manager
- C.Fabric Manager
- D.Connectrix Manager

Correct Answers: C

3: A customer has plugged a new host into his SAN but cannot see the HBA WWNs appear in the Topology. What are two [2] ways to resolve?

- A.Reset the switch
- B.Rediscover the switch
- C.Enable SNMP on the switches
- D.Install the Host Agent and wait for the host to be discovered

Correct Answers: B D

4: Which database service needs to be verified if EMC VisualSAN 4.0 displays errors on program start?

- A.Oracle 8i
- B.Informix 9
- C.Sybase 11
- D.SQL Server 2000

Correct Answers: D

5: Which two [2] management tools have SAN zoning capabilities in a McDATA environment?

- A.Connectrix Manager
- B.Fabric Control Watch
- C.Embedded Web Server
- D.Storage Virtualization Control

Correct Answers: A C

6: From Connectrix Manager, which two [2] levels of user rights can be assigned to specific users?

- A.Fabric Administrator
- B.System Administrator
- C.Product Administrator
- D.Configuration Administrator

Correct Answers: B C

7: Which version of HBA firmware must be used with PowerPath?

- A.Current HBA firmware
- B.Firmware shipped with HBA
- C.Latest HBA Firmware from vendor
- D.Current approved EMC HBA firmware

Correct Answers: D

8: In the OSI 7-layer Network Model, which layer describes the cabling used to create Fibre Channel SANs?

- A.Layer 1, Physical
- B.Layer 2, Data Link
- C.Layer 3, Network
- D.Layer 6, Presentation

Correct Answers: A

9: What is the recommended minimum amount of memory in a management station for an EMC VisualSAN 4.0 installation in a mid-sized SAN?

- A.256 MB
- B.512 MB
- C.1 GB
- D.2 GB

Correct Answers: C

10: How many buffer-to-buffer (BB) credits can be used on ports 4-23 in a DS-24M2 switch?

- A.5
- B.12
- C.24
- D.60

Correct Answers: A

11: Which native command on a B-series switch will provide data for EMC Customer Service?

- A.showtech
- B.supportshow
- C.supportlogs
- D.switchsupport

Correct Answers: B

12: A new HBA is added to a Sun Solaris host. After a reconfiguration reboot, the new HBA is logged into the FA port on the Symmetrix, but it cannot see any devices. Which two [2] must be verified?

- A.Correct HBA WWN and FA association exists in the VCMDDB
- B.LUN number conversion from hexadecimal to decimal in the sd.conf file
- C.LUN number conversion from decimal to hexadecimal in the sd.conf file
- D.LUN number conversion from hexadecimal to decimal in HBA driver configuration file on the host

Correct Answers: A B