



Exam Code: HP0-091

Exam Name: HP-UX System Administration

Vendor: HP

Version: DEMO

Part: A

1: How do you set up a device swap area and ensure it is active at each system startup?

- A. Start device swapping using the swapon command on an existing file system mount point.
- B. Start device swapping using the swapon command on a logical volume; add an entry to the /etc/fstab file.
- C. Start device swapping using the swapon command on a logical volume; add an entry to the /etc/sstab file.
- D. Start device swapping using the swapon command on a logical volume; add an entry to the /etc/vfstab file.

Correct Answers: B

2: Which commands can be used to create device files? Select TWO.

- A. mkdevice
- B. insf
- C. fsadm
- D. mksf
- E. devstart

Correct Answers: B D

3: What is the purpose of the lost+found directory?

- A. allows fsck to recover orphaned files and directories
- B. required on JFS file systems for journaling
- C. functions as a trash can for the file system
- D. a temporary storage for deleted files

Correct Answers: A

4: Which command is used to recreate the /stand/system file?

- A. system_prep
- B. mkkernal
- C. vi system
- D. frecover
- E. sysgen

Correct Answers: A

5: Which level is used by fbackup to complete a full backup?

- A. 0
- B. 1
- C. 9
- D. F
- E. V

Correct Answers: A

6: How does root allow an ordinary user to add/remove printers in SAM?

- A. not possible
- B. edit sam.allow
- C. set the UID bit
- D. establish a restricted build

Correct Answers: D

7: Place the steps to install a fibre channel card in the correct order.

Order the correct steps to install a fibre channel card.

Steps	Order
install driver	place step 1 here
boot system	place step 2 here
run ioscan	place step 3 here
install hardware	place step 4 here
shutdown	place step 5 here

Correct Answers:

Order the correct steps to install a fibre channel card.

Steps	Order
install driver	install driver
boot system	install hardware
run ioscan	shutdown
install hardware	run ioscan
shutdown	boot system

8: If /tmp is 100% full, which commands are used to determine its volume location and if free space is available on that disk?

- A. bdf, vgdisplay
- B. lvdisplay, diskinfo
- C. bdf, lvdisplay, pvdisplay

D.vgdisplay, lvdisplay, diskinfo

Correct Answers: C

9: Order the steps required to perform a complete integrity check of a journaled file system.

Order the steps required to perform a complete integrity check of a journaled file system /data

Steps	Steps in order
<code>mount /data</code>	place step 1 here
<code>fsck -F jfs -o full,nolog /data</code>	place step 2 here
<code>fsck -F /data</code>	place step 3 here
Check the lost+found directory for orphans	place step 4 here
Close all open files and directories	place step 5 here
<code>umount /data</code>	
<code>shutdown -r now</code>	

Correct Answers:

Order the steps required to perform a complete integrity check of a journaled file system /data

Steps	Steps in order
<code>mount /data</code>	<code>fsck -F /data</code>
<code>fsck -F jfs -o full,nolog /data</code>	Close all open files and directories
<code>fsck -F /data</code>	<code>shutdown -r now</code>
Check the lost+found directory for orphans	<code>mount /data</code>
Close all open files and directories	Check the lost+found directory for orphans
<code>umount /data</code>	
<code>shutdown -r now</code>	

10: During a run-state change from run level 1 to run level 2 , which script would be run last?

A./sbin/rc2.d/K900nfs.server

B./sbin/rc2.d/S500inetd

C./sbin/rc2.d/S430nfs.client

D./sbin/rc2.d/K200tps.rc

E./sbin/rc2.d/S620xfs

Correct Answers: E