



Exam Code: HP0-094

Exam Name: HP-UX Networking and Security

Vendor: HP

Version: DEMO

Part: A

1: When mounting a file system from an NFS client, which configuration file is used to name the local mount point?

- A.fstab
- B.nfstab
- C.exports
- D.nfs.conf

Correct Answers: A

2: What is the meaning of the following ARP table entry?

```
# arp -a
```

```
foo (10.0.0.2) at (incomplete)
```

- A.Node foo only supports proxy ARP.
- B.The ARP table entry for node foo has expired.
- C.An ARP request was sent for node foo, but there was no ARP response.
- D.An ARP request was sent for node foo, but only a partial response was received.

Correct Answers: C

3: How should you grant NFS filesystem access to individual users as opposed to all users?

- A.create a group accessible mount point
- B.specify a netgroup in the /etc/exports file
- C.add the users to the /etc/exports file using the form host:uid/gid
- D.add the users to the /etc/exports file using the form host:username

Correct Answers: B

4: Which protocol allows your server to discover the IP address of another server based on the other server's name?

- A.ARP
- B.PPP
- C.DNS
- D.DHCP
- E.Bootstrap

Correct Answers: C

5: What is used for the implementation of Internet name designations as specified in RFC 1034 and RFC 1035?

- A.INS
- B.BIND
- C.SIND
- D.DHCP

Correct Answers: B

6: A customer reports that pings to node FOO take a long time, then fail with "unknown host".

Of the options given, what is the next logical troubleshooting step?

- A.telnet FOO
- B.nslookup FOO
- C.ps -ade | grep ping
- D.ping the IP address of FOO

Correct Answers: B

7: Which directory does the template for your new sendmail.cf file reside?

- A./etc/mail/
- B./etc/mail/sendmail/
- C./usr/share/sendmail-cf/
- D./usr/newconfig/etc/mail/
- E./var/templates/shared/mail/

Correct Answers: D

8: Given the following configuration in the named zone file:

```
hp.com                IN  MX  10  tiger.hp.com
                       IN  MX  20  mail.hp.com
                       IN  MX  30  relay.hp.com
```

Assuming tiger.hp.com is NOT accessible through the firewall, which statement is true regarding messages addressed to tiger.hp.com?

- A.Incoming mail will be returned to sender as undeliverable.
- B.Incoming mail will arrive on mail and will be forwarded to relay waiting on tiger.
- C.Incoming mail will arrive on tiger but will not be accessible until the firewall is turned off.
- D.Incoming mail will arrive on mail and will be forwarded to tiger as it becomes accessible.

Correct Answers: D

9: When you start the sendmail service, you would like to have the mail written to /var/adm/syslog/mail.log. What should you do?

- A.Modify the mail.conf file to add the new location.
- B.No special action is required because that is the default location.
- C.Append -oL/var/adm/syslog/mail.log to the end of command line.
- D.Append -f/var/adm/syslog/mail.log to the end of the command line.
- E.Append -lf/var/adm/syslog/mail.log to the end of the command line.

Correct Answers: B

10: When you set up an 8 CPU DHCP server, how many subnets can you configure per pool?

- A.1
- B.2
- C.4
- D.8

Correct Answers: A

11: Which states are valid for DHCP? (Select two.)

- A.init
- B.select
- C.rebind
- D.reboot
- E.broadcast

Correct Answers: D E

12: Which combination of NFS mount options provides the best chance of avoiding client hangs?

- A.retry=2,hard
- B.retry=4,soft
- C.retry=6,hard,intr
- D.retry=3,retrans=6

Correct Answers: B

13: Which command dismounts an NFS mounted filesystem?

- A.mount -r /mnt
- B.unmount /mnt
- C.mntab -x /mnt
- D.umount server:/mnt

Correct Answers: D

14: During the configuration process for sendmail, which command is run to determine the default hostname to be used for delivery?

- A.uname -s
- B.getuname
- C.sendmail -h
- D.hostname -s
- E.gethostname

Correct Answers: E

15: What does the DHCP device group allow for?

- A.automatic startup of DHCP tools
- B.multiple subnets to be specified for each pool
- C.callback routines within the /etc/dcptab file
- D.different types of clients to receive different parameters

Correct Answers: D