



**Exam Code:** HP0-310

**Exam Name:** OpenView Performance Insight

**Vendor:** HP

**Version:** DEMO

## **Part: A**

- 1: What type of information does the Capacity Planning Report present?
- A.identifies the ten worst performing interfaces and assigns a grade to each interface based on utilization, error, and discard exceptions
  - B.identifies interfaces, devices, locations, and protocols with lowest availability and highest response time
  - C.forecasts busy hour utilization and sort interfaces, devices, locations, or protocols by rate of growth
  - D.provides utilization, error, and discard data for one or more active interfaces that you select from a list of active interfaces

**Correct Answers: C**

- 2: OVPI integration with NNM can support \_\_\_\_\_. Select TWO.
- A.launching polling policy manager from the NNM GUI
  - B.launching of OVPI collectors by NNM
  - C.viewing of OVPI reports using NNM object menus
  - D.importing a node list from NNM
  - E.running OVPI applications through NNM Web Console

**Correct Answers: C D**

- 3: Which report provides a solution for a possible Cisco device re-indexing incident?
- A.Interface Reporting
  - B.System Resources
  - C.Cisco Service Assurance Agent Reporting
  - D.Cisco MPLS VPN

**Correct Answers: A**

- 4: What are the major differentiating factors for OVPI when compared to fault management applications? Select TWO.
- A.real time ad-hoc displays
  - B.long term low frequency polling
  - C.data discarded once the problem is resolved
  - D.immediate information on the current situation
  - E.analytical summarization of past conditions

**Correct Answers: B E**

- 5: After installation, Sybase will produce messages on startup. Where are these messages placed?
- A.{DPIPE\_HOME}\log\
  - B.{SYBASE}\install\
  - C.{SYBASE}\log\
  - D.{DPIPE\_HOME}\install\log\

**Correct Answers: B**

6: When an SNMP device is not showing up in the report, what would you check for? Select TWO.

- A.Check to see if OVPI can still access the device by SNMP.
- B.Check to see if the community string in the device has changed.
- C.Check to see if the device can be accessed using telnet.
- D.Check to see if the device will still send out SNMP Traps.

**Correct Answers: A B**

7: Which situation could lead to an empty report?

- A.The data tables for the report do not exist in Sybase.
- B.The user is not allowed to view this particular data.
- C.The system time on the user's system is not correct.
- D.An incorrect OVPI server is being used.

**Correct Answers: B**

8: A report may be displayed, but none of the report elements are populated. There are several reasons for this, two of these reasons could be \_\_\_\_\_. Select TWO.

- A.the time stamp on the data is incorrect
- B.database has filled up
- C.OVPI license size is incorrect
- D.reports are being run before the data is ready

**Correct Answers: B D**

9: Where would you check to verify why reports are not being generated?

- A.{DPIPE\_HOME}\log\ovpi.log, Catalog View Manager
- B.Catalog View Manager, {DPIPE\_HOME}\log\trend.log
- C.{TREND\_LOG}\trend.log, Schedules
- D.{OVPI\_LOG}\trend.log, Schedules

**Correct Answers: C**

10: If a report is displayed, but the elements of the report are not populated (graphs, tables ?), what would you do? Select TWO.

- A.check to see if rollups are still in progress.
- B.check to see if the application server is running
- C.run the report in Viewer or Builder and check for time range
- D.check trend.log file for report generation errors

**Correct Answers: A C**