



Exam Code: HP0-553

Exam Name: Servicing HP Entry-level Integrity Servers

Vendor: HP

Version: DEMO

Part: A

1: How can I read the description for the OpenVMS command "show devices" on HP Integrity server?

- A.rtfmf show devices
- B.help show devices
- C.man show devices
- D.show devices -h

Correct Answers: B

2: What LINUX command is used to get an I/O list on HP Integrity server?

- A.ioscan
- B.showdev
- C.lsdev
- D.scanpci
- E.listio

Correct Answers: D

3: What is the MP/iLO command to power cycle the system?

- A.reset entity - RE
- B.power status - PS
- C.power control - PC
- D.power cycle entity - PE

Correct Answers: C

4: Which MP/iLO commands are used to verify the actual system state?

- A.system status (ss), secure option (so), LAN status (ls), access console (co)
- B.LAN status (ls), LAN configuration (lc), secure option (so), set access (sa)
- C.system status (ss), access console (co), power status (ps), virtual front panel (vfp)
- D.system revision (sysrev), virtual front panel (VFP), LAN configuration (lc), secure option (so)

Correct Answers: C

5: What is the official HP-UX tool on an HP Integrity server to perform an OS image backup?

- A.fbackup
- B.system imager
- C.Ignite-UX
- D.Data Protector
- E.recovery CD/DVD

Correct Answers: C

6: Click the Task button.

Specify the correct sequence to change the boot option order.

Specify the correct sequence of changing the boot order

Term	Definition
(place here)	Select the boot option you want to move
(place here)	Select the "Boot Option Maintenance Menu"
(place here)	Save the settings to NVRAM and exit
(place here)	Connect to the MP and enter the EFI Boot Manager
(place here)	Select "Change Boot Order"
(place here)	Move the boot option using the up (u) and down (d) keys

1 2 3 4 5 6 Done

Correct Answers:

Specify the correct sequence of changing the boot order

Term	Definition
2	Select the boot option you want to move
1	Select the "Boot Option Maintenance Menu"
5	Save the settings to NVRAM and exit
6	Connect to the MP and enter the EFI Boot Manager
4	Select "Change Boot Order"
3	Move the boot option using the up (u) and down (d) keys

1 2 3 4 5 6 Done

7: What is the proper way to update SAL/PAL firmware?

- A.update SAL/PAL firmware as separate items
- B.replace the system board
- C.load the complete firmware bundle
- D.SIDK how to update SAL/PAL firmware

Correct Answers: C

8: What is a function of ODE?

- A.MAPPER lists the hardware installed in the server

B.CPU_EXER tests the CPU for cache problems

C.MEM_EXER tests the memory for MBE

D.DOWNLOAD upgrades EFI firmware

Correct Answers: A

9: Which I/O ports are located on the system board on a HP Integrity rx2600 server? Select THREE.

A.System LAN port

B.console LAN port

C.SCSI port

D.DB-25 port

E.VGA port

F.USB port

Correct Answers: A C F

10: What is the correct way of updating the Host Bus Adapter (HBA) firmware?

A.there is no way to update firmware

B.replace ROM on the interface card

C.use online/offline tools

D.replace card with newer version

Correct Answers: C