



**Exam Code:** NS0-920

**Exam Name:** Network Appliance NetCache Deployment  
Options and Streaming

**Vendor:** Network Appliance

**Version:** DEMO

## Part: A

1: What version(s) of SSH does NetCache support?

- A. Versions 1 and 2
- B. Version 2 only
- C. Versions 2 and 3
- D. Version 3 only
- E. None

**Correct Answers: A**

2: Which set of acceleration rules will best allow for acceleration of a Windows Media Server that uses MMS and HTTP for transport protocols?

NetCache IP: 10.1.2.3 netcache.server.com

Streaming Server IP: 10.1.2.5 m.server.com

- A. streaming.acceleration.rules=\n10.1.2.3 1755 \* \* 10.1.2.5 1755 m.server.com \*\n10.1.2.3 80 \* \* 10.1.2.5 80 m.server\n\n
- B. config.streaming.acceleration.rules=\n10.1.2.3 1755 \* \* 10.1.2.5 1755 m.server.com \*\n\nconfig.http.acceleration.rules=\n10.1.2.3 80 \* \* 10.1.2.5 80 m.server.com \*\n\n
- C. config.acceleration.rules=\nmms 10.1.2.3 10.1.2.5 netcache.server.com m.server.com\nhttp 10.1.2.3 10.1.2.5 netcache.server.com m.server.com\n\n
- D. config.streaming.acceleration.rules=\n10.1.2.3 554 \* \* 10.1.2.5 554 m.server.com \*\n10.1.2.3 80 \* \* 10.1.2.5 80 m.server.com \*\n\n

**Correct Answers: A**

3: What happens if you assign a service group ID of 4 on one NetCache appliance, and you assign a service group ID of 2 on another NetCache appliance?

- A. The two groups will load balance between each other.
- B. The WCCP router will automatically group the two together.
- C. Each NetCache appliance will join a different service group.
- D. The NetCache appliances use only the ID assignment for internal information, so there is no effect.

**Correct Answers: C**

4: Which three are true about WCCP? (Choose 3)

- A.WCCP service groups must support a single protocol.
- B.WCCP service groups can consist of one or more routers or proxy-cache servers.
- C.WCCP service groups must be defined with the same settings.
- D.Traffic redirection and distribution are based on logical WCCP service groups.

**Correct Answers: B C D**

5: What is the purpose of the "Here I Am" message?

- A.It identifies the NetCache appliance as the router.
- B.It identifies the service group membership.
- C.It announces that the NetCache appliance is available after a shutdown.
- D.It identifies that the NetCache appliance has received a request.

**Correct Answers: B**

6: When traffic is tunneled, the NetCache appliance can take which two actions? (Choose 2)

- A.It can be used with manually configured browsers.
- B.It passes specified types of nonstandard traffic through without caching it.
- C.It examines the source and destination information, and caches the resulting objects.
- D.It receives requests and allows or denies based on ACLs.

**Correct Answers: B D**

7: When is information recorded into the Streaming Access log?

- A.When the client streaming connection is opened.
- B.Within 500 ms of connect.
- C.Throughout the streaming session.
- D.When the client streaming connection is closed.

**Correct Answers: D**

8: When you have a Digital Rights Management (DRM) streaming, authentication is performed between which two devices?

- A.HTTP server and client player
- B.streaming media server and client player
- C.authentication server and router
- D.domain controller and streaming media server

**Correct Answers: B**

9: A list of HTTP headers returned to a client for a cache hit on a stream may be viewed using the \_\_\_\_\_.

- A.smstats command
- B.sysstat command
- C.Streaming Details log
- D.object command

**Correct Answers: D**

10: Bandwidth allocation rules can be used to optimize streaming performance in which three

ways? (Choose 3)

- A.They can allocate bandwidth by user and group.
- B.They can manage NetCache bandwidth utilization to ensure bandwidth for other uses.
- C.They can allocate bandwidth based on CPU and memory usage.
- D.They can restrict or deny connections.

**Correct Answers: A B D**

11: Which statement about a Layer 4 switch is true? (Choose 3)

- A.It can be configured to pass non-HTTP traffic directly to the Web.
- B.It passes traffic based on the port number in a TCP/IP packet.
- C.It passes traffic based on the URL of the client's request.
- D.It uses MAC address rewriting to redirect packets.

**Correct Answers: A B D**

12: Request forwarding is useful for doing which of the following?

- A.To process URLs that are not cacheable, or for sites that use IP authentication.
- B.To force all traffic through the NetCache appliance.
- C.To create a load balancing scheme.
- D.To allow the NetCache to send the URL request as if it is coming from the cache and not the client.

**Correct Answers: A**

13: Why must a Layer 4 switch be on the same subnet as the NetCache appliance?

- A.To use IP-GRE encapsulation.
- B.To prevent IP spoofing.
- C.To use MAC address rewriting.
- D.To monitor the health of the NetCache appliance.

**Correct Answers: C**

14: How will the following configuration command affect the factory default configuration?  
set config.http.transparency on

- A.NetCache starts listening promiscuously on port 80.
- B.NetCache stops listening on port 3128 and restarts listening promiscuously on port 3128.
- C.An error message is reported; no configuration change occurs.
- D.An error message is reported; NetCache starts listening promiscuously on all TCP ports.

**Correct Answers: B**

15: Which can be determined about an .ASF object by using the object command?

- A.The playing time of the stream.
- B.The amount of disk space used to store it on the cache.
- C.The number of packets in the stream.
- D.The author of the stream.

**Correct Answers: C**