An engineer is configuring a dedicated SSID for onboarding devices. Which SSID type accomplishes this configuration?

- A. dual
- B. hidden
- C. broadcast
- D. quest

Correct Answer: A

QUESTION 67

An administrator is configuring RADIUS on a Cisco switch with a key set to Cisc403012128 but is receiving the error "Authentication failed: 22040 Wrong password or invalid shared secret. "what must be done to address this issue?

- A. Add the network device as a NAD inside Cisco ISE using the existing key.
- B. Configure the key on the Cisco ISE instead of the Cisco switch.
- C. Use a key that is between eight and ten characters.
- D. Validate that the key is correct on both the Cisco switch as well as Cisco ISE.

Correct Answer: D

QUESTION 68

A Cisco ISE server sends a CoA to a NAD after a user logs in successfully using CWA Which action does the CoA perform?

- A. It terminates the client session
- B. It applies the downloadable ACL provided in the CoA
- C. It applies new permissions provided in the CoA to the client session.
- D. It triggers the NAD to reauthenticate the client

Correct Answer: B

QUESTION 69

A new employee just connected their workstation to a Cisco IP phone. The network administrator wants to ensure that the Cisco IP phone remains online when the user disconnects their Workstation from the corporate network Which CoA configuration meets this requirement?

- A. Port Bounce
- B. Reauth
- C. NoCoA
- D. Disconnect

Correct Answer: C

QUESTION 70

An administrator is configuring cisco ISE lo authenticate users logging into network devices using TACACS+ users are able to log into the network devices?

- A. Enable the device administration service in the Administration persona
- B. Enable the session services in the administration persona
- C. Enable the service sessions in the PSN persona.

D. Enable the device administration service in the PSN persona.

Correct Answer: D

QUESTION 71

An administrator is trying to collect metadata information about the traffic going across the network to gam added visibility into the hosts. This Information will be used to create profiling policies for devices us mg Cisco ISE so that network access policies can be used What must be done to accomplish this task?

- A. Configure the RADIUS profiling probe within Cisco ISE
- B. Configure NetFlow to be sent to me Cisco ISE appliance.
- C. Configure SNMP to be used with the Cisco ISE appliance
- D. Configure the DHCP probe within Cisco ISE

Correct Answer: D

QUESTION 72

A customer wants to set up the Sponsor portal and delegate the authentication flow to a third party for added security while using Kerberos Which database should be used to accomplish this goal?

- A. RSA Token Server
- B. Active Directory
- C. Local Database
- D. LDAP

Correct Answer: B

QUESTION 73

Which two features must be used on Cisco ISE to enable the TACACS, feature? (Choose two)

- A. Device Administration License
- B. Server Sequence
- C. Command Sets
- D. Enable Device Admin Service
- E. External TACACS Servers

Correct Answer: AD

QUESTION 74

An engineer is configuring sponsored guest access and needs to limit each sponsored guest to a maximum of two devices. There are other guest services in production that rely on the default guest types. How should this configuration change be made without disrupting the other guest services currently offering three or more guest devices per user?

- A. Create an ISE identity group to add users to and limit the number of logins via the group configuration.
- B. Create a new guest type and set the maximum number of devices sponsored guests can register

300-715 Exam Dumps 300-715 PDF Dumps 300-715 VCE Dumps 300-715 Q&As https://www.ensurepass.com/300-715.html

- C. Create an LDAP login for each guest and tag that in the guest portal for authentication.
- D. Create a new sponsor group and adjust the settings to limit the devices for each guest.

Correct Answer: D

QUESTION 75

Which two external identity stores support EAP-TLS and PEAP-TLS? (Choose two.)

- A. Active Directory
- B. RADIUS Token
- C. Internal Database
- D. RSA SecurID
- E. LDAP

Correct Answer: AE

QUESTION 76

An engineer is configuring Cisco ISE and needs to dynamically identify the network endpoints and ensure that endpoint access is protected. Which service should be used to accomplish this task?

- A. Profiling
- B. Guest access
- C. Client provisioning
- D. Posture

Correct Answer: A

QUESTION 77

Which statement about configuring certificates for BYOD is true?

- A. An Android endpoint uses EST, whereas other operating systems use SCEP for enrollment
- B. The SAN field is populated with the end user name.
- C. An endpoint certificate is mandatory for the Cisco ISE BYOD
- D. The CN field is populated with the endpoint host name

Correct Answer: C

QUESTION 78

An organization is hosting a conference and must make guest accounts for several of the speakers attending. The conference ended two days early but the guest accounts are still being used to access the network. What must be configured to correct this?

- A. Create an authorization rule denying sponsored guest access.
- B. Navigate to the Guest Portal and delete the guest accounts.
- C. Create an authorization rule denying guest access.
- D. Navigate to the Sponsor Portal and suspend the guest accounts.

Correct Answer: D

QUESTION 79

What is a valid guest portal type?

- A. Sponsored-Guest
- B. My Devices
- C. Sponsor
- D. Captive-Guest

Correct Answer: A

QUESTION 80

An engineer is configuring the remote access VPN to use Cisco ISE for AAA and needs to conduct posture checks on the connecting endpoints After the endpoint connects, it receives its initial authorization result and continues onto the compliance scan What must be done for this AAA configuration to allow compliant access to the network?

- A. Configure the posture authorization so it defaults to unknown status
- B. Fix the CoA port number
- C. Ensure that authorization only mode is not enabled
- D. Enable dynamic authorization within the AAA server group

Correct Answer: D

QUESTION 81

Which configuration is required in the Cisco ISE authentication policy to allow Central Web Authentication?

- A. MAB and if user not found, continue
- B. MAB and if authentication failed, continue
- C. Dot1x and if user not found, continue
- D. Dot1x and if authentication failed, continue

Correct Answer: A

QUESTION 82

There is a need within an organization for a new policy to be created in Cisco ISE. It must validate that a specific anti-virus application is not only installed, but running on a machine before it is allowed access to the network. Which posture condition should the administrator configure in order for this policy to work?

- A. file
- B. registry
- C. application
- D. service

Correct Answer: C

QUESTION 83

An engineer is configuring 802.1X and is testing out their policy sets. After authentication, some endpoints are given an access-reject message but are still allowed onto the network. What is causing this issue to occur?