

## Answer Area

App service plan setting	Value
Number of VM instances	<div><div></div><div>▼</div><div>2</div><div>4</div><div>8</div><div>16</div></div>
Pricing tier	<div><div></div><div>▼</div><div>Isolated</div><div>Standard</div><div>Premium</div><div>Consumption</div></div>

### QUESTION 88

#### HOTSPOT

You develop a news and blog content delivery app for Windows devices.

A notification must arrive on a user's device when there is a new article available for them to view.

You need to implement push notifications.

How should you complete the code segment? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

## [Download Full Version AZ-204 Exam Dumps\(Updated in Feb/2023\)](#)

### Answer Area

```
string notificationHubName = "contoso_hub";
string notificationHubConnection = "connection_string";

    hub =
        NotificationHubClient
        NotificationHubClientSettings
        NotificationHubJob
        NotificationDetails

    .
        NotificationHubClient
        NotificationHubClientSettings
        NotificationHubJob
        NotificationDetails

        GetInstallation
        CreateClientFromConnectionString
        CreateOrUpdateInstallation
        PatchInstallation

(notificationHubConnection, notificationHubName);
string windowsToastPayload =
    @"<toast><visual><binding template=""ToastText01""><text id=""1"">" +
    @"New item to view" + @"</text></binding></visual></toast>";
try
{
    var result =
        await hub.
            SendWindowsNativeNotificationAsync
            SubmitNotificationHubJobAsync
            ScheduleNotificationAsync
            SendAppleNativeNotificationAsync

    ...
}
catch (System.Exception ex)
{
    ...
}
...
```

**Correct Answer:**

## [Download Full Version AZ-204 Exam Dumps\(Updated in Feb/2023\)](#)

### Answer Area

```
string notificationHubName = "contoso_hub";
string notificationHubConnection = "connection_string";
var hub =
    NotificationHubClient
    NotificationHubClientSettings
    NotificationHubJob
    NotificationDetails
    .
    NotificationHubClient
    NotificationHubClientSettings
    NotificationHubJob
    NotificationDetails
    .
    GetInstallation
    CreateClientFromConnectionString
    CreateOrUpdateInstallation
    PatchInstallation
(notificationHubConnection, notificationHubName);
string windowsToastPayload =
    @"<toast><visual><binding template=""ToastText01""><text id=""1"">" +
    @"New item to view" + @"</text></binding></visual></toast>";
try
{
    var result =
        await hub.
            SendWindowsNativeNotificationAsync
            SubmitNotificationHubJobAsync
            ScheduleNotificationAsync
            SendAppleNativeNotificationAsync
            ...
}
catch (System.Exception ex)
{
    ...
}
...
```

### QUESTION 89

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You develop an HTTP triggered Azure Function app to process Azure Storage blob data. The app is triggered using an output binding on the blob.

The app continues to time out after four minutes. The app must process the blob data.

You need to ensure the app does not time out and processes the blob data.

Solution: Update the functionTimeout property of the host.json project file to 10 minutes.

Does the solution meet the goal?

- A. Yes
- B. No

[AZ-204 Exam Dumps](#) [AZ-204 PDF Dumps](#) [AZ-204 VCE Dumps](#) [AZ-204 Q&As](#)

<https://www.ensurepass.com/AZ-204.html>

## **[Download Full Version AZ-204 Exam Dumps\(Updated in Feb/2023\)](#)**

**Correct Answer:** B

**Explanation:**

Instead pass the HTTP trigger payload into an Azure Service Bus queue to be processed by a queue trigger function and return an immediate HTTP success response.

Note:

Large, long-running functions can cause unexpected timeout issues. General best practices include:

Whenever possible, refactor large functions into smaller function sets that work together and return responses fast. For example, a webhook or HTTP trigger function might require an acknowledgment response within a certain time limit; it's common for webhooks to require an immediate response. You can pass the HTTP trigger payload into a queue to be processed by a queue trigger function. This approach lets you defer the actual work and return an immediate response.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-functions/functions-best-practices>

### **QUESTION 90**

You are developing an Azure Function App that runs in an App Service Plan. The Azure Function is triggered by a Timer object. You observe that the Azure Function does not reliably trigger when scheduled. Which two actions should you perform?

- A. Verify that Always On is enabled.
- B. Modify the trigger to use a SignalR trigger.
- C. Ensure that the function has a retry configured.
- D. Modify the trigger to use Consumption mode instead of the App Service plan.

**Correct Answer:** AC

### **QUESTION 91**

You are developing an application that allows users to find musicians that are looking for work. The application must store information about musicians, the instruments that they play, and other related data.

The application must also allow users to determine which musicians have played together, including groups of three or more musicians that have performed together at a specific location.

Which Azure Cosmos DB API should you use for the application?

- A. Core
- B. MongoDB
- C. Cassandra
- D. Gremlin

**Correct Answer:** B

## [Download Full Version AZ-204 Exam Dumps\(Updated in Feb/2023\)](#)

### **QUESTION 92**

You are developing a mobile instant messaging app for a company.

The mobile app must meet the following requirements:

- Support offline data sync.
- Update the latest messages during normal sync cycles.

You need to implement Offline Data Sync.

Which two actions should you perform? Each correct answer presents part of the solution.

NOTE: Each correct selection is worth one point.

- A. Retrieve records from Offline Data Sync on every call to the PullAsync method.
- B. Retrieve records from Offline Data Sync using an Incremental Sync.
- C. Push records to Offline Data Sync using an Incremental Sync.
- D. Return the updatedAt column from the Mobile Service Backend and implement sorting by using the column.
- E. Return the updatedAt column from the Mobile Service Backend and implement sorting by the message id.

**Correct Answer:** BE

#### **Explanation:**

B: Incremental Sync: the first parameter to the pull operation is a query name that is used only on the client. If you use a non-null query name, the Azure Mobile SDK performs an incremental sync. Each time a pull operation returns a set of results, the latest updatedAt timestamp from that result set is stored in the SDK local system tables. Subsequent pull operations retrieve only records after that timestamp.

E (not D): To use incremental sync, your server must return meaningful updatedAt values and must also support sorting by this field. However, since the SDK adds its own sort on the updatedAt field, you cannot use a pull query that has its own orderBy clause.

References:

<https://docs.microsoft.com/en-us/azure/app-service-mobile/app-service-mobile-offline-data-sync>

### **QUESTION 93**

You have an application that includes an Azure Web app and several Azure Function apps. Application secrets including connection strings and certificates are stored in Azure Key Vault.

Secrets must not be stored in the application or application runtime environment. Changes to Azure Active Directory (Azure AD) must be minimized.

You need to design the approach to loading application secrets.

What should you do?

- A. Create a single user-assigned Managed Identity with permission to access Key Vault and configure each App Service to use that Managed Identity.
- B. Create a single Azure AD Service Principal with permission to access Key Vault and use a client secret from within the App Services to access Key Vault.
- C. Create a system assigned Managed Identity in each App Service with permission to access Key Vault.

[AZ-204 Exam Dumps](#) [AZ-204 PDF Dumps](#) [AZ-204 VCE Dumps](#) [AZ-204 Q&As](#)

<https://www.ensurepass.com/AZ-204.html>