

Vendor: CompTIA

Exam Code: N10-008

Exam Name: CompTIA Network+ Certification Exam

Version: 13.02

Q & As: 264

# **QUESTION 1**

A network requirement calls for segmenting departments into different networks. The campus network is set up with users of each department in multiple buildings. Which of the following should be configured to keep the design simple and efficient?

- A. MDIX
- B. Jumbo frames
- C. Port tagging
- D. Flow control

## Correct Answer: C

# **QUESTION 2**

Which of the following devices would be used to manage a corporate WLAN?

- A. A wireless NAS
- B. A wireless bridge
- C. A wireless router
- D. A wireless controller

## Correct Answer: D

# **QUESTION 3**

A wireless network was installed in a warehouse for employees to scan crates with a wireless handheld scanner. The wireless network was placed in the corner of the building near the ceiling for maximum coverage However users in the offices adjacent lo the warehouse have noticed a large amount of signal overlap from the new network Additionally warehouse employees report difficulty connecting to the wireless network from the other side of the building; however they have no issues when lhey are near the antenna Which of the following is MOST likely the cause?

- A. The wireless signal is being refracted by the warehouse's windows
- B. The antenna's power level was set too high and is overlapping
- C. An omnidirectional antenna was used instead of a unidirectional antenna
- D. The wireless access points are using channels from the 5GHz spectrum

# Correct Answer: A

#### **QUESTION 4**

A network device is configured to send critical events to a syslog server; however, the following alerts are not being received:

- Severity 5 LINK-UPDOWN: Interface 1/1, changed state to down
- Severity 5 LINK-UPDOWN: Interface 1/3, changed state to down

Which of the following describes the reason why the events are not being received?

- A. The network device is not configured to log that level to the syslog server
- B. The network device was down and could not send the event
- C. The syslog server is not compatible with the network device

D. The syslog server did not have the correct MIB loaded to receive the message

# Correct Answer: A

## QUESTION 5

A company requires a disaster recovery site to have equipment ready to go in the event of a disaster at its main datacenter. The company does not have the budget to mirror all the live data to the disaster recovery site. Which of the following concepts should the company select?

- A. Cold site
- B. Hot site
- C. Warm site
- D. Cloud site

Correct Answer: C

## **QUESTION 6**

Given the following information:

Protocol	Local address	Foreign address	State
TCP	127.0.0.1:57779	Desktop-Open: 57780	Established
TCP	127.0.0.1:57780	Desktop-Open: 57779	Established

Which of the following command-line tools would generate this output?

- A. netstat
- B. arp
- C. dig
- D. tracert

Correct Answer: A

#### **QUESTION 7**

The management team needs to ensure unnecessary modifications to the corporate network are not permitted and version control is maintained. Which of the following documents would BEST support this?

- A. An incident response plan
- B. A business continuity plan
- C. A change management policy
- D. An acceptable use policy

Correct Answer: C

#### **QUESTION 8**

A user tries to ping 192.168.1.100 from the command prompt on the 192.168.2.101 network but gets the following response: U.U.U.U. Which of the following needs to be configured for these

N10-008 Exam Dumps N10-008 PDF Dumps N10-008 VCE Dumps N10-008 Q&As

networks to reach each other?

- A. Network address translation
- B. Default gateway
- C. Loopback
- D. Routing protocol

#### Correct Answer: B

## **QUESTION 9**

A company is being acquired by a large corporation. As part of the acquisition process, the company's address should now redirect clients to the corporate organization page. Which of the following DNS records needs to be created?

- A. SOA
- B. NS
- C. CNAME
- D. TXT

# Correct Answer: C

## **QUESTION 10**

Which of the following is used to provide networking capability for VMs at Layer 2 of the OSI model?

- A. VPN
- B. VRRP
- C. vSwitch
- D. VIP

#### Correct Answer: C

#### **QUESTION 11**

A technician needs to configure a Linux computer for network monitoring. The technician has the following information:

Linux computer details:

Interface	IP address	MAC address
eth0	10.1.2.24	A1:B2:C3:F4:E5:D6

#### Switch mirror port details:

Interface	IP address	MAC address
eth1	10.1.2.3	A1:B2:C3:D4:E5:F6

After connecting the Linux computer to the mirror port on the switch, which of the following commands should the technician run on the Linux computer?

#### A. ifconfig ecth0 promisc

# N10-008 Exam Dumps N10-008 PDF Dumps N10-008 VCE Dumps N10-008 Q&As https://www.ensurepass.com/N10-008.html

- B. ifconfig eth1 up
- C. ifconfig eth0 10.1.2.3
- D. ifconfig eth1 hw ether A1:B2:C3:D4:E5:F6

## Correct Answer: A

## **QUESTION 12**

A network technician needs to correlate security events to analyze a suspected intrusion Which of the following should the technician use?

- A. SNMP
- B. Log review
- C. Vulnerability scanning
- D. SIEM

#### Correct Answer: D

## **QUESTION 13**

A company wants to implement a large number of WAPs throughout its building and allow users to be able to move around the building without dropping their connections Which of the following pieces of equipment would be able to handle this requirement?

- A. A VPN concentrator
- B. A load balancer
- C. A wireless controller
- D. A RADIUS server

Correct Answer: A

#### **QUESTION 14**

To comply with industry requirements, a security assessment on the cloud server should identify which protocols and weaknesses are being exposed to attackers on the Internet. Which of the following tools is the MOST appropriate to complete the assessment?

- A. Use tcpdump and parse the output file in a protocol analyzer.
- B. Use an IP scanner and target the cloud WAN network addressing.
- C. Run netstat in each cloud server and retrieve the running processes.
- D. Use nmap and set the servers' public IPs as the targets.

Correct Answer: D

# **QUESTION 15**

A network administrator is installing a wireless network at a client's office. Which of the following IEEE 802.11 standards would be BEST to use for multiple simultaneous client access?

## A. CDMA

B. CSMA/CD

N10-008 Exam Dumps N10-008 PDF Dumps N10-008 VCE Dumps N10-008 Q&As https://www.ensurepass.com/N10-008.html