

Exam Code: 920-234

Exam Name: Nortel VPN Router Rls.7.0 Configuration &

Management (NCSS)

Vendor: Nortel

Version: DEMO

Part: A

1: A customer has a VPN Router 1750 with VPN tunneling capabilities.

They want to enable subscribers to have user tunnel connections to the router.

Which parameter must be configured to implement user tunnels on a VPN Router?

A.a user group

B.LDAP group settings

C.password group settings

D.an IP address assignment

E.tunneling protocols settings

Correct Answers: D

2: An engineer wants to configure a firewall policy on the VPN router, and wants to change the system-wide rules that are applied and processed first by the firewall.

Which Stateful Firewall rules need to be modified?

A.Implied Rules

B.Default Rules

C.Override Rules

D.Interface-specific Rules.

Correct Answers: C

3: Which three VPN Router models support the "SSL VPN Module 1000" hardware option card? (Choose three.)

A.VPN Router 1050

B.VPN Router 1100

C.VPN Router 1750

D.VPN Router 2750

E.VPN Router 5000

Correct Answers: C D E

4: A customer would like to use a VPN Router 1750 for SSL VPN and offload encryption onto multiple hardware accelerator cards.

Which statement is true?

A.The 1750 chassis does not support the SSL VPN module or the hardware accelerator card.

B.SSL VPN module and hardware accelerator cards can not be used in the same 1750 chassis.

C.The 1750 chassis does support the SSL VPN module but only a single hardware accelerator card.

D.The 1750 chassis does not support the SSL VPN module but multiple hardware accelerator cards could be installed.

Correct Answers: C

5: A customer has just purchased a VPN Router 1750. They want to know how much RAM it has "out-of-the-box" and if it can be upgraded.

Which statement is true?

A.The VPN Router 1750 chassis comes with 256MB installed and is not upgradeable.

B.The VPN Router 1750 chassis comes with 128MB of RAM installed and is upgradeable to 512MB.

C.The VPN Router 1750 chassis comes with 256MB of RAM installed and is upgradeable to 512MB.

D.The VPN Router 1750 chassis comes with 128MB of RAM installed and is upgradeable to 256MB.

Correct Answers: D

6: A customer has just purchased a VPN Router. They want to know which License Keys are available and what functions each individual key enables.

Which statement is true?

A. The Advanced Routing key enables RIP, OSPF and VRRP functions.

B.The Premium Routing key activates OSPF, VRRP, DLSw and BGP routing functions.

C.The BGP Routing key enables Border Gateway Protocol routing and Data Link Switching capabilities.

D.The VPN Router Stateful Firewall key enables stateful firewall capabilities but disables the standard VPN Router firewall functions.

Correct Answers: B

7: On a VPN Router Rls. 7.0 system, on which two interface types can the routing protocols RIP, OSPF and VRRP be enabled? (Choose two.)

A.Single HSSI

B.Single or Dual V.35

C.10/100 Ethernet port, System Board

D.10/100 Ethernet port, Expansion Module

Correct Answers: C D

8: Which three QoS features are available on the VPN Router? (Choose three.)

A.CLIP

B.DiffServ

C.Demand Services

D.Forwarding Priority

E.Resource Reservation Protocol

Correct Answers: B D E

9: Which three statements are true regarding IPSec Mobility? (Choose three.)

A.VPN tunnel connections survive lost packets.

B.IPSec Mobility is activated with the Advance Routing license key.

C.For IPSec Mobility to work, any VPN Client version can be running.

D.NAT Traversal and IPSec Fail-over will not interoperate with IPSec Mobility.

E.IPSec Mobility is provisioned at the VPN Router, and the settings are pushed down from the server.

Correct Answers: ABE

- 10: When configuring the VPN Router 1750 system, how are the management IP address and subnet mask initially configured?
- A.The management IP address and subnet mask are configured by using the serial interface.
- B.The management IP address and subnet mask will be automatically provided by a DHCP server.
- C.When powered up, the VPN Router will initially be configured with a default management IP address and subnet mask.
- D.Having the management IP address and subnet mask configured is not initially required and can

ERROR: rangecheck

OFFENDING COMMAND: xshow

STACK:

[44 39 22 39 44 44 29 24 44 44 29 39 43 22 29 29 44 67 22 39 22 63 39 44 22 44 29 44 63 34 39 2922 39 24 22 39 44 43 24 25 67 39 0] (be configured from a web browser at anytime.)