



Exam Code: ew0-200

Exam Name: extreme networks associate(ena)

Vendor: Extreme Networks

Version: DEMO

Part: A

1: Which CLI command would you use to create a default route with a metric of 5 and a gateway of 10.0.0.1?

- A.CONFIG IPRROUTE ADD DEFAULT 10.0.0.1 5
- B.CONFIG IPRROUTE ADD DEFAULT 5 10.0.0.1
- C.CREATE IPRROUTE ADD DEFAULT 10.0.0.1 5
- D.CREATE IPRROUTE ADD DEFAULT 5 10.0.0.1

Correct Answers: A

2: An Extreme Switch is shipped with a pre-configured VLAN called DEFAULT that has all switch ports as tagged members.

- A.TRUE
- B.FALSE

Correct Answers: B

3: How would you stop a scheduled configuration download from happening? Use the CLI command:

- A.cancel configuration download
- B.download configuration cancel
- C.configuration download cancel
- D.delete configuration download

Correct Answers: B

4: Given the following information, select the option that would allow you to change the active ExtremeWare version to 6.1.9b11 upon reboot.

```
sysName: Summit5iTx
sysLocation:
sysContact: support@extremenetworks.com, +1 888 257 3000
System MAC: 00:01:30:97:F1:00

License: Full L3 + Security.
System Mode: 802.1Q EtherType is 8100 (Hex). CPU Tx-Priority=High
Recovery Mode: none
Random Early Drop Probability: 0
DLCS: disabled
Current time: Thu Feb 28 15:37:30 2002
Timezone: [Auto DST Enabled] GMT Offset: 0 minutes, DST is not in effect.
Boot time: Thu Feb 28 14:07:06 2002
Next reboot: None scheduled
Timed upload: None scheduled
Timed download: None scheduled
Temperature: Normal. All fans are operational.
Power supply: PSU-A OK, PSU-B failed

Software image selected: secondary
Software image booted: secondary
Primary Software version: 6.1.9b11
Secondary software version: 6.1.7b9

Configuration selected: primary
Configuration booted: primary
Primary configuration: Empty
Secondary configuration: Empty
```

- A.use image primary
- B.download config primary
- C.use config primary
- D.download image primary

Correct Answers: A

5: The default administrator login name for a new Extreme switch was entered as ADMIN (all caps). This will allow the administrator access to the CLI.

A.TRUE

B.FALSE

Correct Answers: B

6: ExtremeWare, pre-installed on every Extreme Networks ?chipset switch, combines industry standard protocols to ensure interoperability with legacy switches and routers, QoS for bandwidth management and traffic prioritization in today networks.

A.TRUE

B.FALSE

Correct Answers: A

7: Which step would you take to configure a VLAN to only allow IP-related traffic?

A.config <vlan> protocol ip

B.config protocol <vlan> ip

C.config ip protocol <vlan>

D.None of these.

Correct Answers: A

8: Extreme Networks switches build their forwarding database from the incoming packet field information containing the:

A.Source MAC address.

B.Destination MAC address.

C.Source IP address.

D.Destination IP address.

Correct Answers: A

9: The CLI console port utilizes a serial cable for physical switch to terminal connection.

A.TRUE

B.FALSE

Correct Answers: A

10: Which CLI command will you use to change the CLI prompt from the default display to Switch02?

A.CONFIG SNMP SYSLOCATION Switch02

B.CONFIG SNMP SYSNAME Switch02

C.CONFIG CLI PROMPT Switch02

D.CONFIG CLI DISPLAY Switch02

Correct Answers: B

11: In spanning tree, the designated bridge is the bridge with the:

- A.least-cost path to the root bridge
- B.highest bridge priority
- C.lowest port cost on all ports
- D.None of these

Correct Answers: A

12: In ExtremeWare, active VLANs that are configured with ports and an IP address and configured to forward IP and run a routing protocol will have their subnet advertised.

- A.TRUE
- B.FALSE

Correct Answers: A

13: A 802.1Q tag is a marker inserted between the source and destination MAC addresses fields of the Ethernet frame.

- A.TRUE
- B.FALSE

Correct Answers: B

14: Which of the following protocol filter/s is/are predefined in ExtremeWare?

- A.OSPF
- B.TCP
- C.NETBIOS
- D.All of these

Correct Answers: C

15: What CLI command is used to disable learning of incoming RIP routes on an interface?

- A.disable rip learning <VLAN>
- B.configure rip rxmode none <VLAN>
- C.configure rip interface <VLAN> passive
- D.None of these

Correct Answers: B