



Exam Code: HP0-742

Exam Name: OpenView Storage Area Manager

Fundamentals

Vendor: HP

Version: DEMO

Part: A

1: After the HP OpenView Storage Area Manager Bridge is reconfigured, ____.

- A.the bridge service must be restarted
- B.the service files are updated automatically
- C.the bridge Device Plug-In (DPI) must be re-deployed
- D.the bridge and Host Agent services must be restarted

Correct Answers: A

2: The HP OpenView Storage Area Manager Bridge is ____.

- A.an integration module for storage Host Agents
- B.developed for external collection of host services
- C.provided as a point of integration for external applications
- D.part of the HP OpenView Storage Area Manager core enabling management server to Host Agent communications

Correct Answers: C

3: Which four HP OpenView applications have pre-defined integrations with HP OpenView Storage Area Manager? (Choose four.)

- A.Reporter
- B.OmniBack
- C.Operations
- D.Service Desk
- E.Data Protector
- F.Network Node Manager
- G.Internet Usage Manager

Correct Answers: A C D G

4: Which two levels of device status are reported for devices without full Device Plug-Ins (DPIs) support? (Choose two.)

- A.Critical
- B.Normal
- C.Warning
- D.Unknown/Unreachable

Correct Answers: B D

5: Which file can be edited to specify the location of the SOLID Server database?

- A.solid.ini
- B.solid.cfg
- C.SanManager.ini
- D.SanManager.cfg

Correct Answers: A

6: HP OpenView Storage Area Manager discovers devices through _____. (Choose two.)

- A.DIAL on the SAN hosts
- B.SNMP from the SAN hosts
- C.DIAL on the management server
- D.SNMP from the management server
- E.API queries to the fibre channel infrastructure devices

Correct Answers: A D

7: Proper installation of a Device Plug-In (DPI) requires stopping and restarting which service?

- A. HP OpenView SAM Bridge
- B. HP OpenView SAM HostAgent
- C. HP OpenView SAM Embedded DB
- D. HP OpenView SAM ManagementServer

Correct Answers: D

8: What does the Device Discovery and Topology (DDT) component do? (Choose two.)

- A. stores device and topology data in a log file
- B. sends alerts based on topology map changes
- C. uses SNMP to discover IP-based storage elements
- D. uses DIAL on the SAN hosts to discovery in-band storage elements

Correct Answers: C D

9: With the use of the Software Development Kit (SDK), any device vendor can create a _____ that enables previously unsupported devices to be monitored by HP OpenView Storage Optimizer.

- A. script
- B. trigger
- C. property file
- D. Device Plug-In (DPI)

Correct Answers: D

10: The Host Agent runs on each host connected to the SAN and communicates to the management server via _____.

- A. RMI
- B. RPC
- C. JDBC
- D. SNMP

Correct Answers: A