



**Exam Code:** NS0-170

**Exam Name:** Network Appliance NetCache Exam

**Vendor:** Network Appliance

**Version:** DEMO

## Part: A

1: A complete listing of Network Appliance support centers is available at \_\_\_\_\_.

- A. [www.netapp.com](http://www.netapp.com)
- B. [ftp.netapp.com](ftp://ftp.netapp.com)
- C. [now.netapp.com](http://now.netapp.com)
- D. NetCache online help

**Correct Answers: C**

2: The NetCache appliance may be used for all of the following EXCEPT \_\_\_\_\_.

- A. HTTP URL filtering
- B. SMTP proxy
- C. DNS caching
- D. NFS caching

**Correct Answers: B**

3: Which TWO vendors?content filtering databases are supported on the NetCache?

- A. SurfControl
- B. WebWasher
- C. Secure Computing
- D. TrendMicro

**Correct Answers: B C**

4: Which one of the following services is not a service supported by ICAP?

- A. Virus scanning of content received through HTTP.
- B. Virus scanning of email content
- C. URL filtering
- D. Active content stripping

**Correct Answers: B**

5: Network Appliance field alerts \_\_\_\_\_ and \_\_\_\_\_.

- A. are available at "[www.netapp.com](http://www.netapp.com)"
- B. may be received via email
- C. are available at "[now.netapp.com](http://now.netapp.com)"
- D. replace autosupport

**Correct Answers: B C**

6: Network Appliance maintains a record of customer product information on the NOW site and this data is \_\_\_\_\_ .

- A. available to anyone with NOW access
- B. only available to authorized users
- C. available only during business hours
- D. only available to NetApp support staff

**Correct Answers: B**

7: Which one of the following NetCache appliances has a maximum storage capacity of 504G Bytes?

A.C1200

B.C2100

C.C6200

D.All the above

**Correct Answers: B**

8: Which TWO of the following statements are equivalent?

A.set config.http.ports "8080" "8081"

B.set config.http.ports \ 8080

8081

\

C.set config.http.ports // 8080 , 8081 \

D.set config.http.ports "8080 , 8081"

**Correct Answers: A B**

9: Which one of the following methods can be used to manage the NetCache appliance but cannot be used to access the Command Line Interface (CLI)?

A.Console

B.Telnet

C.rsh

D.HTTP

**Correct Answers: D**

10: Which command would you use to see the available option choices for the show config.http.acl command?

A.help

B.show config.http.acl.?

C.config.acl help

D.help config.acl

**Correct Answers: B**

11: When configuring a NetCache as a reverse proxy, you must \_\_\_\_ .

A.write one or more acceleration rules

B.reconfigure the client's browser

C.write one or more ACLs

D.have an acceleration license

**Correct Answers: A**

12: When configured as an accelerator, the NetCache appliance is typically located close to the \_\_\_\_\_.

A.client(s)

- B.gateway
- C.server
- D.resolver

**Correct Answers: C**

13: The traceroute command is used to \_\_\_\_ .

- A.report interface activity in Kbps
- B.show the state of each interface
- C.print the route packets take to a network host
- D.display a list of active sockets for each protocol

**Correct Answers: C**

14: You must \_\_\_\_ to reach the NetCache firmware prompt ("OK prompt").

- A.press Esc
- B.enter the halt command
- C.set the environment variable, floppy-boot?, to off
- D.enter the prompt command

**Correct Answers: B**

15: The \_\_\_\_ command displays performance statistics, such as the current CPU usage, the amount of network I/O, and the amount of disk I/O.

- A.ifstat
- B.netstat
- C.stat
- D.sysstat

**Correct Answers: D**